

TAN.WASH-1S-26

Single Stage 2600 Litre
Washdown Separator



Capacity	2600 Litre
Length	2890mm
Width	1260mm
Height	1360mm
Flow Rate	20 litres/min

Information

Ideal for Commercial Carwash use.

Washdown and Silt separators are used to remove dirty water from a car wash or other cleaning facility.

The washdown and silt separator removes the water and any solids, like silt, before they enter the foul drain.

Made in the UK out of high strength polyethylene, their shallow dig depth makes them easy to install and maintain, as well as being ideal for areas with a high-water table.

Specification

- ✓ Lightweight Rotational moulded HDPE construction
- ✓ Shallow dig
- ✓ Separates and retains sediment, silt, and hydrocarbons from vehicle washdown areas
- ✓ Single and multistage units available to optimise performance per application
- ✓ Easy access for emptying and cleaning
- ✓ Ideal for tool hire depots, car and pressure washers, sportsground equipment wash facilities, fleet maintenance and valeting

Please Note The waste separated from vehicle washing and cleaning businesses can be classified as 'contaminated waste'. As such there is a duty of care to dispose/recycle this waste responsibly through a registered waste carrier to a suitably licensed facility.



High Quality
British-Made
Tanks



10 Year
Warranty



Suitable for
8 Vehicles
per hour

TAN.WASH-1S-26

Single Stage 2600 Litre Washdown Separator

You may also need

OPTIONAL EXTRAS



Telescopic neck



Pedestrian Lid



Vehicle Lid



Mains Hydrocarbon Alarm



Mains Silt Alarm

