

TAN.WASH-1S-52

Single Stage 5200 Litre
Washdown Separator



Capacity	5200 Litre
Length	2710mm
Width	2710mm
Height	1725mm
Flow Rate	50 litres/min

Information

Ideal for Brushwash/
Agricultural Equipment use.

Washdown and Silt separators
are used to remove dirty water
from a car wash or other
cleaning facility.

The washdown and silt
separator removes the water
and any solids, like silt, before
they enter the foul drain.

Made in the UK out of high
strength polyethylene, their
shallow dig depth makes them
easy to install and maintain, as
well as being ideal for areas
with a high-water table.

Specification

- ✓ Lightweight Rotational moulded HDPE construction
- ✓ Shallow dig
- ✓ Separates and retains sediment, silt, and hydrocarbons from vehicle washdown areas
- ✓ Single and multistage units available to optimise performance per application
- ✓ Easy access for emptying and cleaning
- ✓ Ideal for tool hire depots, car and pressure washers, sportsground equipment wash facilities, fleet maintenance and valeting

Please Note The waste separated from vehicle washing and cleaning businesses can be classified as 'contaminated waste'. As such there is a duty of care to dispose/recycle this waste responsibly through a registered waste carrier to a suitably licensed facility.



High Quality
British-Made
Tanks



10 Year
Warranty



Suitable for
12 Vehicles
per hour

TAN.WASH-1S-52

Single Stage 5200 Litre Washdown Separator

You may also need

OPTIONAL EXTRAS



Telescopic neck



Vehicle Lid



Mains Silt Alarm



Pedestrian Lid



Mains Hydrocarbon Alarm



Tel: 0330 999 1100

Email: sales@atlantistanks.co.uk

www.atlantistanks.co.uk